

### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

- 1. Features
  - LAN, Bluetooth 2.4 2.5 GHz (2.4 2.5 GHz Antenna for WLAN, Bluetooth, etc.)
  - Compact Size
  - High Efficiency
  - Surface Mount Device
  - Embossed Reel Package
- 2. Part Number

RAC00024-R

3200 (3200-piece T&R)

- 3. Shape, Dimensions and Weight
- 3.1. Shape







#### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

3.2. Dimensions

w 12.5 x d 7.25 x h 1.9 mm





3.3. (Weight)

0.22 g Typical

- 3.4. Plating None
- 3.5. Type Split Ring
- 4. RF Characteristics
- 4.1. Frequency Range 2.4 - 2.5 GHz
- 4.2. Impedance  $50\Omega$
- 4.3. VSWR (Voltage Standing Wave Ratio)50x30mm VSWR (VSWR characteristics of the antenna on a referenceboard of 50 x 30mm)



<sup>2</sup> 

© California Eastern Laboratories April 2021



#### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

VSWR < 2.0 (Frequency Range: 2.4 – 2.5 GHz)



4.4 Radiation Efficiency

 $50x30mm \cdot \zeta$  (Radiation efficiency of theantenna mounted on a reference board of 50 x 30mm, excluding cable and feeder line loss)

Radiation Efficiency > 85 % Frequency Range: 2.4 - 2.5 GHz



3 © California Eastern Laboratories April 2021



### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

#### 4.5. Radiation Pattern:

50x30mm Radiation pattern of the antenna mounted on areference board of 50 x 30mm



Radiation Pattern @2.45 GHz







blue line: Horizontal Polarization red line: Vertical Polarization

4



### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

- 5. Environmental Conditions
- 5.5. Operating Temperature Range

-40 °C to +125 °C

5.6. Storage Conditions

IEC 61760-2

Stock Temperature Range

+5 °C to +40 °C

Relative Humidity10 % to 75 %

6. Recommended Land Pattern and Reference Board



Reference Board

<sup>5</sup> 



### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

#### 7. Recommended Reflow Temperature Profile

	Temperature	Heating Time
Preheating Temperature	180 to 200 °C Max	120s Max
Main Heating Temperature	220 °C Max	50s Max
Peak Temperature	250 °C Max	-



Heating time



### 2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure

- 8. Packaging
- 8.5. Package Quantity: 3,200 pieces/reel
- 8.6. Embossed Reel Dimensions



#### 8.7. Tape Dimensions



#### **Revision History**

Version	Date	Revision
Α	23 April 2021	Initial Version
В	29 August 2022	Name Change



2.4 GHz Metamaterial-Inspired Antenna using a Split Ring Resonator structure